










PLACE STONE LOOK

MAN AND NATURE Place slate-effect porcelain stoneware represents the most advanced synthesis between technological know-how and natural emotion.

- CAESAR MADE IN USA 03
 - INSPIRATION 05
 - PHOTO GALLERY 07
 - RANGE 23



ADVANTAGES





Created for the USA market Exclusive products and collections designed to meet the needs of American consumers.



Top logistic and service Market presence, quick distribution, improved customer service.

The USA have always represented a priority market for Caesar, since its foundation in 1988. Starting in **1997**, the company has a branch office and a warehouse located in **New** Jersey (Eatontown) company owned Caesar USA Inc. Over the years, Caesar's service in the USA has increased in a capillary way with the opening of new logistic hubs in Florida and California.

This path goes on in 2016 with the local production of porcelain collections dedicated to the American market. These products are manufactured in the **brand-new** plant located in Tennessee (MT Pleasant) owned by Gruppo Concorde, which Caesar is part of.

DESIGNED IN ITALY

The materials, specifically thought for the American market are **designed in Italy** thanks to the **unique know-how** that the company has developed over years of activity.

MADE IN USA

The industrial production is in the USA offering considerable logistic **advantages** to the entire distribution network.

offered to American clients.

- _ On one hand, the style and technical avant-garde of a design developed by Caesar in Italy.
- _ On the other hand, the logistic and commercial advantages of a made in the USA product.



Avant-garde technology

Modern and state of the art production sites: maximum quality, efficiency, care of the workers and of the environment.



Style, Design, trend The Italian ceramic tradition interprets American taste to create products featuring unique appeal and certified reliability.



A broad range


The made in the USA products enrich the broad range of Caesar Made in Italy products, with more than 2400 items, 240 colors and more than 30 sizes.

MADE IN USA

Thanks to the strategy **Designed in Italy Made in USA**, Caesar offers doubles the advantages

PORCELAIN STONEWARE

SIZES



COLORS

PLACE is the final goal on a path that abounds with dedication and technical skills.

Searching the world for stones of resolute character and unique personality. Identifying the most stunning slabs and features, seizing their beauty, to return it in an even more authentic state of perfection with the utmost fidelity; recreate the multiple three-dimensional structures of the surface. Each Place slab encapsulates all the beauty and versatility of nature: a world of colors, reliefs, veining and details.












SHALE








SHALE CONTEMPORARY DESIGN AND NATURAL LOOK

PLAC

SHALE

The material offers a genuine natural feel, also thanks to the surface structures that have a richly varied movement.









WIDE RANGE OF COLORS AND HUES

AMBER

Each piece is rich in colors and graphics that stand out when installed on floors, showing the aesthetic variability typical of the most precious slates.










RUST


A

STYLE AND FUNCTIONALITY IN PUBLIC SPACE



Caesar's porcelain stoneware is an elegant and functional material, also for the floors of public spaces.









BATHROOM WALLS FOR IMPRESSIVE EFFECT

4

1



ALMOND

Thanks to its 3 sizes, 2 types of mosaics and harmonious color combinations, the Place range allows to interpret bathroom ambiances for major aesthetical effect.















]] Porcelain Stoneware Floor



Wall

DECORS











Rectified Tile

TRIMS

N0 V.O.C



Low water absorption (<0,5%)



PLACE



12"x12"_Tozzetto size 2"x 2"



3″x24″_Bullnose



6"x12"_Covebase








Porcelain Stoneware Floor Wall

Substantial Variation

DECORS









N0 V.O.C



✵ Frost Proof




Low water absorption (<0,5%)



PLACE









TRIMS










Porcelain Stoneware Floor

]}

Substantial Variation

Wall

DECORS















₩ Frost Proof




Low water absorption (<0,5%)



PLACE






TRIMS












Floor Porcelain Stoneware Wall

DECORS





V4









* Frost Proof





TRIMS 3″x24″_Bullnose 6"x12"_Covebase




STONE LOOK

COLORED-BODY PORCELAIN TILES - RECTIFIED

Colored-body porcelain stoneware tiles are produced minimizing the color difference between the glaze and the body. Nevertheless, the design is visible only on the surface.





Matt / rectified one caliber

PACKAGING	

INCHES	MM	PCS	SURFACE (SQF)	SURFACE (SQM)	WEIGTH (LBS)	WEIGTH (KG)	BOXES	SURFACE (SQF)	SURFACE (SQM)	WEIGTH (LBS)	WEIGTH (KG)
18"x36"	457x914	3	13,08	1,215	~53,57	~24,3	36	470,88	43,74	~1928,52	~874,8
24"x24"	610x610	3	11,62	1,08	~47,62	~21,6	40	464,8	43,2	~1904,8	~864
12"x24"	305x610	7	13,56	1,26	~55,55	~25,2	40	524,4	50,4	~2222	~1008

		V0

Very Uniform appearance. Pieces of the same shade value are very uniform and smooth in texture. They can be measured for small color differences and are in compliance with the color uniformity requirements of tables 6-10 (ANSI A137.1-2012)

_	_	 _	_	
-		_		V1
	H			

Uniform Appearance. Differences among pieces from the same production run are minimal. colors.



texture on each piece may vary significantly. It is recommended

that the range be viewed before selection.

Slight Variation. Clearly distinguishable texture and/or pattern within similar While the colors and/or textures present on a single piece of tile will be indicative of the colors and/or texture to be expected on the other tiles, the amount of colors and/or

V4 Substantial Variation.

Random color and/or texture differences from tile to tile, so that one tile may have totally different colors and/or textures from that on other tiles. Thus, the final installation will be unique. It is recommended that the range be viewed before selection.

Color reproductions may vary from actual products.

Caesar reserves the right to modify the products illustrated in this catalogue for reasons of production or to improve quality. Samples are purely indicative. Packaging and weights may vary for production reasons. Contact our sales department when ordering.

In case of running pattern installation, Caesar recommends a maximum 33% offset.

Caesar warrants that our products meet or exceed the requirements of ANSI, specification ANSI A137.1: 2012, as shown in our Tile Performance Data sheets.

TILE PERFORMANCE DATA

COLORED-BODY PORCELAIN TILES - RECTIFIED CLASSIFICATION IN ACCORDANCE WITH ANSI A137.1: 2012 (P1 CLASS).

	TECHNICAL FEATURE	ASTM TEST	VALUE REQUIRED ANSI A 137.1-2012	CAESAR AVERAGE VALUE	
	Facial dimension	ASTM C-499	±0,5% o ±2,0 mm		
+	Thickness	ASTM C-499	0,040 inch max (1 mm)		
	Wedging	ASTM C-502	≤ 0,5% (+/- 2 mm)	In accordance to ANSI A 137.1-2012	
	Warpage diagonal	ASTM C-485	≤ 0,5% (+/- 2 mm)	in accordance to ANSEA 137.1-2012	
↓ ↓	Warpage edge (for tile <610x610 mm)	ASTM C-485	±0,40% or ±1,3 mm		
	Warpage edge (for tile >610x610 mm)	ASTM C-485	±0,40% or ±1,8 mm		
	Water absorption	ASTM C-373	≤ 0,5%	Passed "impervious tiles" Class P1	
	Breaking strength	ASTM C-648	≥ 250 lbs (>=1113 N)	>=400 lbs	
	Freeze thaw	ASTM C-1026	No damages	In accordance	
	Chemical resistance	ASTM C-650	As reported	Unaffected	
	MOHS hardness			Coeff. 6	
	BOOT 3000 DCOF *	BOOT 3000	0,42	In accordance	

Average values referred to the last two years of production and related to the matt finish of the product. Values relate to the matt finish of the product and to tests carried out by certified external laboratories, whose results are available upon request at Headoffice. Be sure to use the same caliber tiles. Color reproductions may vary from actual products. * Due to the intrinsic nature of porcelain stoneware tiles, please note that the coefficient of friction may vary within the same production lot or from one production lot to the other. Caesar products can become slippery when wet. We recommend to always keep the surface dry.



CLEANING PROCEDURES

- After 36/48 hours, when both the floor and the grouts have completed their first drying phase and before the real phase of the floor has yet to begin, it is necessary to proceed with the cleaning of the tiled surface using a "padding" action acid detergent, diluted according to the manufacturer's instructions.
- For areas heavily stained with grout, it is necessary to repeat this operation once or twice, increasing the percentage of water.
- The excess grout residue must be removed so that it does not dry and stick on the surface. It is necessary to change the cleaning water frequently and rinse well.
- Care must be taken on inlayed, polished and anti-slip products; for the latter in particular, the use of a floor-washing machine combined with the action of an acid detergent helps reach the spaces between adjacent tiles and clean them properly.
- If such a cleaning procedure is not carried out, or if such cleaning is carried out too late, the grout residue creates an extremely absorbent film, which holds dirt, making the surface difficult to clean: in this case, Ceramiche CAESAR S.p.A. will not be liable for any damage caused to the surface.
- We would like to remind you that porcelain stoneware is a product with excellent technical features which allow for high grade of mechanical wear and resistance to acids (except for hydrofluoric acid and its derivatives) and alkalis, features which are added to a high aesthetic quality.
- Ordinary maintenance must be carried out using specialist detergents to remove stains but these detergents must not leave a wax, film or membrane residue.
- Rinsing well with plenty of clean water is a fundamental part of the cleaning procedure, therefore we advise against the use of products which state that they "do not need rinsing".
- For more detailed and updated information, please consult the website www.caesarceramicsusa.com, or contact our sales department.





PORCELAIN STONEWARE

Caesar reserves the right to modify the products illustrated in this catalogue for reasons of production or to improve quality. Samples are purely indicative. Packaging and weights may vary for production reasons. Contact our sales department when ordering.

Caesar warrants that our products meet or exceed the requirements of ANSI, specification ANSI A137.1: 2012, as shown in our Tile Performance Data sheets.

The Caesar complete terms and conditions of sale (including limited warranty) are specified in the price list. Should you need further information, please contact our sales department.



PLACE



CAESAR CERAMICS USA, INC. 35 James Way - Eatontown, NJ 07724 Phone: +1 (732) 389 5757 fax: +1 (732) 389 8589

